



## BRITSEAL SILICONE

High modulus acetox cure silicone in a range of colours to match the BRITFLEXI grout range. BRITSEAL is suitable for sealing a wide range of surfaces and is compatible with most tile types.

### Application Areas/Properties:

- Sealing joints around sanitary ware and tiles in kitchens and bathrooms.
- Sealing of glazed doors and window frames.
- Sealing joints in permanent wet conditions.
- Contains a fungicide for protection against mildew.
- High elasticity.
- Non-slump.
- Adhesion tests prior to application recommended.

### Recommendations:

- Do NOT use on stones sensitive to acids such as limestone. The use of a neutral cure silicone would be recommended for this application.
- Do NOT use for sealing fishtanks or ponds due to BRITSEAL being harmful to aquatic life.
- Do NOT use on bitumen surfaces.

### Application Method:

All surfaces must be dry, clean and free from loose matter. BRITSEAL should be applied to the joint as a continuous bead from the nozzle, which should be cut at a 45° angle as to fill the entire joint. Smooth the surface off with a damp finishing tool before a film starts to form, which is approximately 10 minutes at 23°C, although this time will be reduced at elevated temperatures.

### Packaging:

Available in 300ml cartridges.

### Colours:

White, Jasmine, Beige, Clear, Grey and Black.



ITEM REFERENCE: FBS300(W)



ITEM REFERENCE: FBS300(J)



ITEM REFERENCE: FBS300(B)



ITEM REFERENCE: FBS300(G)



ITEM REFERENCE: FBS300(BLK)

CLEAR

ITEM REFERENCE: FBS300(C)

### Technical Data:

Application Temperature: 5°C - 40°C

Skimming time: 15 mins at 23°C

Resistance to Temperature: -30°C to +150°C

Specific Gravity: 0.98

Coverage: To calculate the number of cartridges required please follow the formula below.

$$\frac{\text{Width (cm)} \times \text{Depth of Joint (cm)} \times \text{Length (m)} \text{ of Joint}}{300}$$

### Storage/Shelf life:

Store unopened in cool, dry conditions. Stored correctly BRITSEAL has a shelf life of 18 months from the date shown on the packaging.

### Health and Safety:

Wear safety gloves and safety glasses.

Notes: The information given is without prejudice and is believed to be accurate and complete. BRIT ADHESIVES goods are guaranteed against defective materials but we have no control over the site conditions, misuse of the product or the quality of the workmanship. BRIT ADHESIVES accepts no liability for any direct or indirect consequential loss or damages arising or resulting from the use of this information. Site conditions should be taken into consideration.

Hainge Road, Tividale.  
West Midlands, B69 2NH

Tel:  
0121 520 9333

Fax:  
0121 520 9050

Web:  
[www.britadhesives.co.uk](http://www.britadhesives.co.uk)

Email:  
[sales@britadhesives.co.uk](mailto:sales@britadhesives.co.uk)