



## BRITGROUT

A White Wall Tile Grout suitable for joints up to 3mm. For joints that are above this width use BRIT FLEXI GROUT. BRITGROUT will give a non-slump, extra fine smooth grout ideal for all types of tiles. Suitable for internal and external use. Water resistant. Conforms to BSEN13888 CG1.

### INTENDED USE:

BRITGROUT is suitable for grouting wall tiles including ceramics, slate, porcelain, limestone, marble and mosaics.

### PREPARATION:

Ensure tiles are securely fixed and that all grout joints are clean. The substrate must be sound and free from any excessive movement. When grouting over a large area that requires the use of more than one bag of BRITGROUT we recommend that the mixes be from the same batch, to give uniformity of colour across the installation.

**WARNING:** Grout can cause staining to certain types of tiles and cause surface discolouration. We recommend the use of a suitable tile protector and advise that the grout be mixed and tried on a spare tile to check compatibility before grouting commences.

### MIXING RATIO:

Add 2.5kg of BRITGROUT into a mixing vessel containing 1lt of clean cold water. BRITGROUT should be mixed either by hand or with a mechanical mixer to form a smooth, lump free mortar. Do not use excessive water during mixing or during the cleandown process as this can lead to poor strength development and efflorescence on the surface of the grout. Work the mortar into the joints with a rubber backed trowel or squeegee ensuring they are completely filled.

### CLEANING:

Remove surplus grout as soon as possible. Any dry film left after cleaning can be removed with a soft dry cloth. Clean tools with water.

### TECHNICAL INFORMATION:

All work should be carried out in accordance with BS5385 and BS8000, The Code of Practice for the installation of floor and wall tiles.

APPLICATION TEMPERATURE: Between 5°C and 30°C	CONTACT WITH WATER: 7 days
POT LIFE: 2 hours*	FULL USE: 24 hours*

\*NOTE - The above times refer to site conditions of 20°C. These times will be increased at lower temperatures and reduced at elevated temperatures.

Hainge Road, Tividale.  
West Midlands, B69 2NH

Tel:  
0121 520 9333

Fax:  
0121 520 9050

Web:  
[www.britadhesives.co.uk](http://www.britadhesives.co.uk)

Email:  
[sales@britadhesives.co.uk](mailto:sales@britadhesives.co.uk)



**WHITE**

ITEM REFERENCE:  
FWTG25  
2.5kg BAG



**WHITE**

ITEM REFERENCE:  
FWTG10  
10kg BAG



# BRITGROUT

A White Wall Tile Grout suitable for joints up to 3mm. For joints that are above this width use BRIT FLEXI GROUT. BRITGROUT will give a non-slump, extra fine smooth grout ideal for all types of tiles. Suitable for internal and external use. Water resistant. Conforms to BSEN13888 CG1.

### COVERAGE:

This will depend on the size of tile and the joint widths and depths. The formula below will give the amount in the form of kg/m<sup>2</sup>

$$\frac{(\text{Tile length (mm)} + \text{Tile Width (mm)}) \times \text{Joint Width (mm)} \times \text{Joint Depth (mm)} \times 1.6}{(\text{Tile length (mm)} \times \text{Tile Width (mm)})}$$

TILE SIZE (MM)	JOINT WIDTH (MM)	
	2	3
600 x 600 x 10	25m <sup>2</sup>	15.6m <sup>2</sup>
330 x 330 x 10	13m <sup>2</sup>	8.6m <sup>2</sup>
150 x 150 x 8	7.4m <sup>2</sup>	5m <sup>2</sup>
24 x 24 x 10	0.9m <sup>2</sup>	0.6m <sup>2</sup>

Common tile sizes and coverage per 2.5kg bag

TILE SIZE (MM)	JOINT WIDTH (MM)	
	2	3
600 x 600 x 10	100m <sup>2</sup>	64.2m <sup>2</sup>
330 x 330 x 10	52m <sup>2</sup>	34.4m <sup>2</sup>
150 x 150 x 8	29.6m <sup>2</sup>	20m <sup>2</sup>
24 x 24 x 10	3.6m <sup>2</sup>	2.4m <sup>2</sup>

Common tile sizes and coverage per 10kg bag (4 x 2.5kg sachets)

### STORAGE:

Store unopened in original packaging in cool, dry conditions. BRITGROUT has a shelf life of 12 months from the date shown on the packaging.

### HEALTH & SAFETY:



Keep away from animals and children. Wet cement can cause irritation, dermatitis and/or burns. Wear suitable protective clothing, gloves, eye/face protection.



PROTECTIVE CLOTHING



WEAR SAFETY GOGGLES



WEAR SAFETY GLOVES

NOTES: The information given is without prejudice and is believed to accurate and complete. BRIT ADHESIVES goods are guaranteed against defective materials but we have no control over the site conditions, misuse of the product or the quality of the workmanship. BRIT ADHESIVES accepts no liability for any direct or indirect consequential loss or damages arising or resulting from the use of this information. Timber subfloors should be installed according to manufacturers' instructions and site conditions should be taken into consideration.

Hainge Road, Tividale.  
West Midlands, B69 2NH

Tel:  
0121 520 9333

Fax:  
0121 520 9050

Web:  
[www.britadhesives.co.uk](http://www.britadhesives.co.uk)

Email:  
[sales@britadhesives.co.uk](mailto:sales@britadhesives.co.uk)